# NSN 5945-01-349-0037

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-349-0037

## **Overall Length:**

3.500 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

2.620 inches single mounting facility and 2.640 inches single mounting facility

# Center To Center Distance Between Mounting Facilities Parallel To Width:

2.750 inches single mounting facility and 2.780 inches single mounting facility

### **Overall Height:**

4.720 inches

**Overall Width:** 

3.130 inches

**Case Material:** 

Plastic

**Environmental Protection:** 

Dustproof and fungus resistant

#### Unthreaded Mounting Hole Diameter:

0.100 inches single mounting facility and 0.200 inches single mounting facility

#### **Fragility Factor:**

Moderately rugged

#### **Contact Material:**

Copper

#### End Application:

4610-01-219-8707 water purification equiptment set

#### **Frequency In Hertz:**

60.0

#### Winding Quantity:

1

## **Purpose For Which Designed:**

General

#### **Coil Quantity:**

1

## Duty Type:

Continuous

## Arc Quenching Method:

Air

# Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

# Storage Type:

General purpose warehouse

# **Cubic Measure:**

51.700 cubic inches

## Mounting Facility Pattern:

Rectangular single mounting facility

# NSN 5945-01-349-0037

Electromagnetic Relay - Page 2 of 2



Nonpile-up Main Contact Arrangement: 3 pole, double throw, one position momentary Time Delay: 20.00 minutes fixed operate time **Operating Voltage Rating And Type At Specificationified Temp:** 120.0 volts ac 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 120.0 ac **Terminal Type And Quantity:** 16 quick disconnect, male all functions Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A03300