## NSN 5945-01-349-1810

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-349-1810

| Overall Length:   |
|---|
| 0.590 inches  |
| Overall Height:   |
| 0.366 inches  |
| Overall Width:  |
| 0.390 inches  |
| Case Material:  |
| Plastic   |
| Environmental Protection:                                     |
| Dustproof   |
| Fragility Factor:   |
| Moderately rugged   |
| Contact Material:   |
| Silver  |
| Contact Surface Treatment:                                    |
| Gold  |
| End Application:  |
| Laser navy up   |
| Winding Quantity:   |
| 1   |
| Purpose For Which Designed:                                   |
| General   |
| Coil Quantity:  |
| 1   |
| Winding Dc Resistance Rating:                                 |
| 125.0 ohms single winding                                     |
| Duty Type:  |
| Continuous  |
| Arc Quenching Method:   |
| Air   |
| Mounting Facility Type And Quantity:                          |
| 1 plug-in terminal single mounting facility                   |
| Storage Type:   |
| General purpose warehouse                                     |
| Cubic Measure:  |
| 0.084 cubic inches  |
| Nonpile-up Main Contact Arrangement:                          |
| 1 pole, double throw, one position momentary                  |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 5.0 volts dc 25 degrees celsius single winding                |
| Main Contact Load Current Rating At Maximum Rated Voltage:    |

5.0 amperes dc resistive load

## NSN 5945-01-349-1810

Electromagnetic Relay - Page 2 of 2



## Main Contact Maximum Voltage Rating In Volts: 500.0 ac Energizing Element Power Rating: 200.0 milliwatts Precious Material And Location: Contacts silver and contact surfaces gold Precious Material: Silver and gold Terminal Type And Quantity: 4 tab, solder lug all functions Shelf Life:

Demilitarization:

**Unit Of Measure:** 

No

N/a

Fiig:

A03300