NSN 5945-01-354-6098

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-354-6098

Overall Length:

5.130 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.312 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.125 inches single mounting facility

Overall Height:

3.700 inches

Overall Width:

3.940 inches

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.218 inches single mounting facility

Winding Quantity:

1

Coil Quantity:

Winding Dc Resistance Rating:

55.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, double throw, one position momentary

Time Delay:

1.00 seconds fixed operate time

Nonpile-up Auxiliary Contact Arrangement:

5 pole, double throw, one position momentary

Auxiliary Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

150.0 amperes ac resistive load and 150.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

208.0 ac and 28.0 dc

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

NSN 5945-01-354-6098

Electromagnetic Relay - Page 2 of 2



Terminal Type Ar	nd Quantity:
------------------	--------------

9 threaded stud contacts

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300