# NSN 5945-01-355-7018

Electromagnetic Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-01-355-7018

**Overall Length:** 

0.375 inches

**Overall Height:** 

0.280 inches

**Overall Width:** 

0.375 inches

#### Winding Quantity:

1

#### **Coil Quantity:**

1

Duty Type:

Continuous

#### Mounting Facility Type And Quantity:

1 plug-in terminal single mounting facility

#### Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

#### **Criticality Code Justification:**

Feat

#### Time Delay:

0.004 seconds fixed release time

# **Operating Voltage Rating And Type At Specificationified Temp:**

18.0 volts dc 25 degrees celsius single winding

# Main Contact Load Current Rating At Maximum Rated Voltage:

200.0 milliamperes dc inductive load

# Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

# **Special Features:**

Failure rate level of 1.0 percent per 10, 000 cycles

# Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

8 wire lead all functions

#### **Specification Data:**

81349-mil-r-39016/19 government specification

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A03300