NSN 5945-01-363-4192

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-363-4192

| Overall Length: |
|----------------------------------------------------------------------------------------------------------|
| 1.718 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.625 inches second mounting facility |
| Overall Height: |
| 1.000 inches |
| Overall Width: |
| 0.937 inches |
| Mounting Slot Width: |
| 0.150 inches second mounting facility |
| Fragility Factor: |
| Moderately rugged |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 3 slotted hole second mounting facility |
| Storage Type: |
| General purpose warehouse |
| Mounting Facility Pattern: |
| Triangle second mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 4 pole, double throw, one position momentary |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 1.396 inches second mounting facility and 1.446 inches second mounting facility |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 115.0 volts ac 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 2.0 amperes ac lamp load and 2.0 amperes dc lamp load |
| Main Contact Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Terminal Type And Quantity: |
| 14 pin all functions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5945-01-363-4192

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300