NSN 5945-01-364-1950

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-364-1950

| Overall Length: |
|---|
| 3.500 inches |
| Overall Height: |
| 2.500 inches |
| Overall Width: |
| 2.250 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.188 inches single mounting facility |
| Fragility Factor: |
| Moderately rugged |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 288.0 ohms single winding |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 21.875 cubic inches |
| Mounting Facility Pattern: |
| In-line single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, double throw, one position momentary |
| Nonpile-up Auxiliary Contact Arrangement: |
| 1 pole, double throw, one position momentary |
| Auxiliary Contact Maximum Voltage Rating In Volts: |
| 250.0 ac |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 24.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 30.0 amperes ac resistive load and 30.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |

240.0 ac and 28.0 dc

NSN 5945-01-364-1950

Electromagnetic Relay - Page 2 of 2



Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

20.0 amperes ac resistive load

Energizing Element Power Rating:

2.0 watts

Terminal Type And Quantity:

8 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300