NSN 5945-01-364-9190

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-364-9190

| Overall Length: 0.275 inches Overall Diameter: 0.370 inches Environmental Protection: Hermetic Fragility Factor: Moderately rugged Contact Material: Gold and platinum |
|---|
| Overall Diameter: 0.370 inches Environmental Protection: Hermetic Fragility Factor: Moderately rugged Contact Material: Gold and platinum |
| 0.370 inches Environmental Protection: Hermetic Fragility Factor: Moderately rugged Contact Material: Gold and platinum |
| Environmental Protection: Hermetic Fragility Factor: Moderately rugged Contact Material: Gold and platinum |
| Hermetic Fragility Factor: Moderately rugged Contact Material: Gold and platinum |
| Fragility Factor: Moderately rugged Contact Material: Gold and platinum |
| Moderately rugged Contact Material: Gold and platinum |
| Contact Material: Gold and platinum |
| Gold and platinum |
| |
| Contact Confess Treatments |
| Contact Surface Treatment: |
| Gold |
| End Application: |
| 6625-01-285-9218 generator, signal |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 1.56 kilohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 9 terminal single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, double throw, one position momentary |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 26.5 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 1.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Terminal Type And Quantity: |
| 9 wire lead all functions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5945-01-364-9190

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300