## NSN 5945-01-365-1232

Electromagnetic Relay - Page 1 of 2

**Overall Length:** 



View Online at https://aerobasegroup.com/nsn/5945-01-365-1232

0.335 inches
Overall Height:
0.398 inches
Overall Width:
0.335 inches
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
1.56 kilohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
9 terminal single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Coil voltage suppression and polarized
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Criticality Code Justification:
Feat
Operating Voltage Rating And Type At Specificationified Temp:
26.5 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
500.0 milliamperes ac resistive load and 1.0 amperes dc resistive load200.0 milliamperes dc inductive load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Special Features:
Failure rate 0.1 percent per 10, 000 cycles
Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5945-01-365-1232

Electromagnetic Relay - Page 2 of 2



Terminal Type And Quantity	[erminal	<b>Type</b>	And	Quantity	<b>/</b> :
----------------------------	----------	-------------	-----	----------	------------

9 wire lead all functions

**Specification Data:** 

81349-mil-r-39016/15 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300