

View Online at <https://aerobasegroup.com/nsn/5945-01-367-4427>

Overall Length:

0.375 inches

Overall Height:

0.477 inches

Overall Width:

0.375 inches

Environmental Protection:

Hermetic

Fragility Factor:

Moderately rugged

End Application:

F15 serd 8321

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

45.0 ohms single winding and 55.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

8 terminal single mounting facility

Storage Type:

General purpose warehouse

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Criticality Code Justification:

Feat

Time Delay:

0.002 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

5.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

500.0 milliamperes ac resistive load and 1.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

Failure rate 3.0 percent per 10,000 cycles

Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 wire lead all functions

Specification Data:

81349-mil-r-39016/17 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300