## NSN 5945-01-371-2556

Electromagnetic Relay - Page 1 of 2

**Overall Length:** 



View Online at https://aerobasegroup.com/nsn/5945-01-371-2556

0.375 inches
Overall Height:
0.300 inches
Overall Width:
0.375 inches
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
End Application:
4935-01-136-0233
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
390.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
8 terminal single mounting facility
Storage Type:
General purpose warehouse
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Criticality Code Justification:
Feat
Time Delay:
0.002 seconds fixed operate time
Operating Voltage Rating And Type At Specificationified Temp:
12.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
100.0 milliamperes dc lamp load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc

## **Test Data Document:**

Failure rate: 0.1 percent per 10, 000 cycles

**Special Features:** 

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5945-01-371-2556

Electromagnetic Relay - Page 2 of 2



Terminal	Type	And (	Quantity:
----------	------	-------	-----------

8 wire lead all functions

**Specification Data:** 

81349-mil-r-39016/17 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300