NSN 5945-01-371-4138

Electromagnetic Relay - Page 1 of 2

Overall Length: 1.320 inches

Overall Height: 0.617 inches Overall Width: 0.410 inches

Mounting Slot Width:

Fragility Factor:
Moderately rugged
Winding Quantity:

0.120 inches single mounting facility



View Online at https://aerobasegroup.com/nsn/5945-01-371-4138

Center To Center Distance Between Mounting Facilities Parallel To Length: 1.062 inches single mounting facility and 1.078 inches single mounting facility

1
Coil Quantity:
1
Winding Dc Resistance Rating:
700.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Polarized
Mounting Facility Pattern:
In-line single mounting facility
In-line single mounting facility Nonpile-up Main Contact Arrangement:
3 ,
Nonpile-up Main Contact Arrangement:
Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary
Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Criticality Code Justification:
Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Criticality Code Justification: Feat
Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Criticality Code Justification: Feat Time Delay:
Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Criticality Code Justification: Feat Time Delay: 0.004 seconds fixed operate and release time
Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Criticality Code Justification: Feat Time Delay: 0.004 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp:
Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Criticality Code Justification: Feat Time Delay: 0.004 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding
Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Criticality Code Justification: Feat Time Delay: 0.004 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage:
Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Criticality Code Justification: Feat Time Delay: 0.004 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 160.0 milliamperes dc lamp load

NSN 5945-01-371-4138

Electromagnetic Relay - Page 2 of 2

A03300



Special Features:
Failure rate 0.1 percent per 10, 000 cycles
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Test Data Document:
81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
8 pin all functions
Specification Data:
81349-mil-r-39016/6 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig: