NSN 5945-01-374-5445

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-374-5445

Overall Length:
1.730 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.625 inches single mounting facility
Overall Height:
2.515 inches
Overall Width:
1.280 inches
Mounting Slot Width:
0.150 inches single mounting facility
Environmental Protection:
Hermetic
End Application:
C17a acft
Winding Quantity:
1
Coil Quantity:
1
Duty Type:
Continuous
Mounting Facility Type And Quantity:
3 slotted hole single mounting facility
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:
0.05 seconds fixed operate and release time
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:
1.396 inches single mounting facility and 1.446 inches single mounting facility
Operating Voltage Rating And Type At Specificationified Temp:
115.0 volts ac 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
2.0 amperes ac motor load and 2.0 amperes dc motor load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Terminal Type And Quantity:
14 pin all functions

NSN 5945-01-374-5445

Electromagnetic Relay - Page 2 of 2



	L -	11		ife	_
3	ne	п	_	пе	Ξ

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300