

View Online at <https://aerobasegroup.com/nsn/5945-01-375-0464>

Thread Class:

2a single mounting facility

Overall Length:

1.079 inches

Overall Height:

1.280 inches

Overall Width:

0.827 inches

Case Material:

Plastic

Fragility Factor:

Moderately rugged

Contact Material:

Silver

Contact Surface Treatment:

Gold flash

End Application:

An/fyq109spad

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

40.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

1 threaded stud single mounting facility

Storage Type:

General purpose warehouse

Thread Size:

0.099 inches single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.02 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

6.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 10.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Energizing Element Power Rating:

900.0 milliwatts

Precious Material And Location:

Contacts silver and contact surfaces gold

Precious Material:

Silver and gold

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

5 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300