## NSN 5945-01-376-0827

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-376-0827

**Thread Class:** 

2b single mounting facility

Thread Length:

0.500 inches single mounting facility

**Overall Length:** 

3.090 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.230 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:** 

1.840 inches single mounting facility

**Overall Height:** 

3.440 inches

**Overall Width:** 

2.660 inches

**End Application:** 

5895-01-310-2545

Frequency In Hertz:

50.0 or 400.0

**Winding Quantity:** 

**Purpose For Which Designed:** 

Specific

**Coil Quantity:** 

**Duty Type:** 

Continuous

**Mounting Facility Type And Quantity:** 

4 threaded hole single mounting facility

**Thread Size:** 

0.164 inches single mounting facility

**Mounting Facility Pattern:** 

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:** 

2 pole, single throw, normally closed, momentary action

**Operating Voltage Rating And Type At Specificationified Temp:** 

120.0 volts ac 25 degrees celsius second winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

## **Test Data Document:**

80063-a3102126 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5945-01-376-0827

Electromagnetic Relay - Page 2 of 2



Thread Series Designator:
Unc single mounting facility
Terminal Type And Quantity:
8 screw all functions
Specification Data:
80063-a3102126 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A03300