NSN 5945-01-382-6369

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-382-6369
Overall Length:
0.370 inches
Overall Height:
0.493 inches
Overall Width:
0.370 inches
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
850.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
10 terminal single mounting facility
Storage Type:
General purpose warehouse
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Criticality Code Justification:
Feat
Operating Voltage Rating And Type At Specificationified Temp:
12.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
250.0 milliamperes ac resistive load and 1.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Special Features:
Failure rate: 0.1 percent per 10, 000 cycles
Test Data Document:
81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
10 wire lead all functions
Specification Data:

N/a

Shelf Life:

81349-mil-r-39016/16 government specification

NSN 5945-01-382-6369

Electromagnetic Relay - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A03300