

View Online at <https://aerobasegroup.com/nsn/5945-01-384-7432>

Overall Length:

0.370 inches

Overall Height:

0.280 inches

Overall Diameter:

0.370 inches

Environmental Protection:

Cold resistant and hermetic and heat resistant and shock resistant and vibration resistant

Winding Quantity:

2

Coil Quantity:

2

Winding Dc Resistance Rating:

500.0 ohms first winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

9 plug-in terminal first mounting facility

Features Provided:

Coil voltage suppression and latching contacts

Nonpile-up Main Contact Arrangement:

2 pole, double throw, two positions momentary

Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius first winding

Minimum Differential Electrical Operating Rating:

7.0 volts

Main Contact Load Current Rating At Maximum Rated Voltage:

500.0 milliamperes ac resistive load and 1.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

9 wire lead energizing element

Specification Data:

81349-mil-r-39016/29-058m government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300