

View Online at <https://aerobasegroup.com/nsn/5945-01-384-7432>

**Overall Length:**

0.370 inches

**Overall Height:**

0.280 inches

**Overall Diameter:**

0.370 inches

**Environmental Protection:**

Cold resistant and hermetic and heat resistant and shock resistant and vibration resistant

**Winding Quantity:**

2

**Coil Quantity:**

2

**Winding Dc Resistance Rating:**

500.0 ohms first winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

9 plug-in terminal first mounting facility

**Features Provided:**

Coil voltage suppression and latching contacts

**Nonpile-up Main Contact Arrangement:**

2 pole, double throw, two positions momentary

**Operating Voltage Rating And Type At Specificationified Temp:**

12.0 volts dc 25 degrees celsius first winding

**Minimum Differential Electrical Operating Rating:**

7.0 volts

**Main Contact Load Current Rating At Maximum Rated Voltage:**

500.0 milliamperes ac resistive load and 1.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Test Data Document:**

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

9 wire lead energizing element

**Specification Data:**

81349-mil-r-39016/29-058m government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300