

View Online at <https://aerobasegroup.com/nsn/5945-01-387-6463>

**Overall Length:**

0.375 inches

**Overall Height:**

0.375 inches

**Overall Diameter:**

Between 0.275 inches and 0.335 inches

**Environmental Protection:**

Hermetic

**Frequency In Hertz:**

60.0 or 400.0

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

400.0 ohms first winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

8 terminal single mounting facility

**Features Provided:**

Coil voltage suppression

**Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

**Operating Current Rating And Type:**

23.6 milliamperes ac first winding

**Time Delay:**

0.0075 seconds fixed release time

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts ac 25 degrees celsius first winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

28.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac

**Test Data Document:**

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

8 pin all functions

**Specification Data:**

81349-mil-r-39016/21 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300