NSN 5945-01-387-6463

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-387-6463

Overall Length:

0.375 inches

Overall Height:

0.375 inches

Overall Diameter:

Between 0.275 inches and 0.335 inches

Environmental Protection:

Hermetic

Frequency In Hertz:

60.0 or 400.0

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

400.0 ohms first winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

8 terminal single mounting facility

Features Provided:

Coil voltage suppression

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

23.6 milliamperes ac first winding

Time Delay:

0.0075 seconds fixed release time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts ac 25 degrees celsius first winding

Main Contact Load Current Rating At Maximum Rated Voltage:

28.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac

Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 pin all functions

Specification Data:

81349-mil-r-39016/21 government specification

Shelf Life:

NSN 5945-01-387-6463

Electromagnetic Relay - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300

