# NSN 5945-01-392-7473

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-392-7473

**Overall Length:** 

0.780 inches

**Overall Diameter:** 

0.370 inches

**Fragility Factor:** 

Moderately rugged

Winding Quantity:

2

**Coil Quantity:** 

2

#### Winding Dc Resistance Rating:

2.0 kilohms all windings

**Duty Type:** 

Continuous

#### Mounting Facility Type And Quantity:

8 terminal single mounting facility

#### Storage Type:

General purpose warehouse

#### **Features Provided:**

Latching contacts

#### Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

#### Criticality Code Justification:

Feat

#### **Operating Voltage Rating And Type At Specificationified Temp:**

26.5 volts dc 25 degrees celsius all windings

#### Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes dc lamp load

## Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

### **Special Features:**

Failure rate: 1.0 percent per 10, 000 cycles

### Test Data Document:

81205-daa3383+132 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

8 wire lead all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

# NSN 5945-01-392-7473

Electromagnetic Relay - Page 2 of 2

**Fiig:** A03300

