NSN 5945-01-394-9482

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-394-9482

| Thread Class: |
|---|
| 2a single mounting facility |
| Thread Direction: |
| Right-hand single mounting facility |
| Overall Length: |
| 1.531 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.187 inches single mounting facility |
| Overall Height: |
| 2.187 inches |
| Overall Width: |
| 0.687 inches |
| Case Material: |
| Metal |
| Environmental Protection: |
| Hermetic |
| Fragility Factor: |
| Moderately rugged |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 2 threaded stud single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 2.300 cubic inches |
| Thread Size: |
| 0.138 inches single mounting facility |
| Mounting Facility Pattern: |
| In-line single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, double throw, one position momentary |
| Time Delay: |
| 0.02 seconds fixed operate and release time |
| Operating Voltage Rating And Type At Specificationified Temp: |

28.0 volts dc 25 degrees celsius single winding

NSN 5945-01-394-9482

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac inductive load and 3.0 amperes dc inductive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

Contacts rated for frequency range 47.5-63hz

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A03300