

View Online at <https://aerobasegroup.com/nsn/5945-01-399-1544>

Overall Length:

1.025 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.446 inches single mounting facility

Overall Height:

1.125 inches

Overall Width:

0.525 inches

Environmental Protection:

Hermetic

Frequency In Hertz:

400.0

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 bracket first mounting facility

Features Provided:

Latching contacts

Nonpile-up Main Contact Arrangement:

2 pole, single throw, both positions maintained

Nonpile-up Auxiliary Contact Arrangement:

2 pole, single throw, both positions maintained

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius first winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.5 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac

Special Features:

Magnetic latch

Test Data Document:

81349-mil-r-83536 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

6 wire hook all functions

Specification Data:

81349-mil-r-83526/13 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300