

View Online at <https://aerobasegroup.com/nsn/5945-01-399-5327>

**Overall Length:**

0.406 inches

**Overall Width:**

2.750 inches

**Unthreaded Mounting Hole Diameter:**

0.138 inches single mounting facility

**Contact Material:**

Silver

**Contact Surface Treatment:**

Gold

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

120.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

6 unthreaded hole single mounting facility

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

48 pole, double throw, one position momentary

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

120.0 ac and 28.0 dc

**Precious Material And Location:**

Contacts silver and contact surfaces gold

**Precious Material:**

Silver and gold

**Test Data Document:**

77327-0032521 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

146 tab, solder lug all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300