# NSN 5945-01-407-7497

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-407-7497

Overall Length:
1.343 inches
Overall Height:
2.004 inches
Overall Width:
1.020 inches
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
290.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
14 plug-in terminal single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Polarized
Nonpile-up Main Contact Arrangement:
4 pole, double throw, one position momentary
Operating Current Rating And Type:
110.0 milliamperes dc single winding
Time Delay:
0.02 seconds fixed release time
Operating Voltage Rating And Type At Specificationified Temp:
28.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
2.0 amperes ac lamp load and 2.0 amperes dc lamp load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Special Features:
Special Features: Failure rate 1.0 percent per 10000 operations

Terminal surfaces gold

## NSN 5945-01-407-7497

Electromagnetic Relay - Page 2 of 2



_							
D,	202	iou		۱Л:	atα	rıa	
ГΙ	CC	IVU	э і	VIC	110	ııa	ı .

Gold

#### **Test Data Document:**

81349-mil-r-83536 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

2 pin energizing element

#### **Specification Data:**

81349-mil-r-83536/16 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A03300