NSN 5945-01-407-7497

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-407-7497

Overall Length:
1.343 inches
Overall Height:
2.004 inches
Overall Width:
1.020 inches
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
290.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
14 plug-in terminal single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Polarized
Nonpile-up Main Contact Arrangement:
4 pole, double throw, one position momentary
Operating Current Rating And Type:
110.0 milliamperes dc single winding
Time Delay:
0.02 seconds fixed release time
Operating Voltage Rating And Type At Specificationified Temp:
28.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
2.0 amperes ac lamp load and 2.0 amperes dc lamp load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Special Features:
Special Features: Failure rate 1.0 percent per 10000 operations

Terminal surfaces gold

NSN 5945-01-407-7497

Electromagnetic Relay - Page 2 of 2



_								
D,	ec	-	10	ΝЛ	21	Δr	12	
ГΙ		IUL	13	IVI	αı	CI.	ıa	ı -

Gold

Test Data Document:

81349-mil-r-83536 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 pin energizing element

Specification Data:

81349-mil-r-83536/16 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300