

View Online at <https://aerobasegroup.com/nsn/5945-01-410-6836>

**Overall Length:**

1.320 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.070 inches single mounting facility

**Overall Height:**

0.410 inches

**Overall Width:**

0.410 inches

**Environmental Protection:**

Cold resistant and heat resistant and shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.120 inches single mounting facility

**End Application:**

Cass station, general electric

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

47.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

2 unthreaded hole single mounting facility

**Features Provided:**

Magnetic shield

**Mounting Facility Pattern:**

In-line single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:**

5.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

2.0 amperes dc resistive load and 100.0 milliamperes ac resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Test Data Document:**

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

8 wire lead all functions

**Specification Data:**

81349--39016/44-002p government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300

**Mil-std (military Standard):**

Mil-prf-39016 spec.