## NSN 5945-01-410-7733

Electromagnetic Relay - Page 1 of 2

1.446 inches single mounting facility

**Environmental Protection:** 

10.0 amperes ac resistive load

10.0 amperes dc resistive loadTerminal Type And Quantity:

8 pin energizing element

115.0 ac and 12.0 dc

Main Contact Maximum Voltage Rating In Volts:

**Auxiliary Contact Load Current Rating At Maximum Rated Voltage:** 

Frequency In Hertz:

Overall Length: 1.718 inches

Overall Height: 1.010 inches Overall Width: 0.515 inches

Hermetic

60.0



View Online at https://aerobasegroup.com/nsn/5945-01-410-7733

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

Winding Quantity:
2
Coil Quantity:
1
Winding Dc Resistance Rating:
88.0 ohms first winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
2 bracket first mounting facility
Pile-up Main Contact Form Arrangement:
1c
Nonpile-up Main Contact Arrangement:
2 two circuit, two positions momentary
Operating Current Rating And Type:
5.0 amperes dc first winding
Nonpile-up Auxiliary Contact Arrangement:
2 two circuit, double break/double make, one position momentary
Auxiliary Contact Maximum Voltage Rating In Volts:
200.00 ac
Operating Voltage Rating And Type At Specificationified Temp:
7.7 volts dc 85 degrees celsius first winding
Main Contact Load Current Rating At Maximum Rated Voltage:

## NSN 5945-01-410-7733

Electromagnetic Relay - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300