# NSN 5945-01-410-8745

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-410-8745

### **Overall Length:**

1.125 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.396 inches single mounting facility and 1.446 inches single mounting facility

#### **Overall Height:**

0.525 inches

#### **Overall Width:**

1.718 inches

#### **Mounting Slot Width:**

0.150 inches single mounting facility

#### **Case Material:**

Metal

**Environmental Protection:** 

Hermetic

#### **Fragility Factor:**

Moderately rugged

## Frequency In Hertz:

50.0 and 60.0 and 400.0

# Winding Quantity:

1

#### **Purpose For Which Designed:**

General

#### **Coil Quantity:**

1

## Duty Type:

Continuous

## Arc Quenching Method:

Air

## Mounting Facility Type And Quantity:

2 slotted hole single mounting facility

## Storage Type:

General purpose warehouse

### **Cubic Measure:**

1.294 cubic inches

## Mounting Facility Pattern:

In-line single mounting facility

## Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

## Operating Current Rating And Type:

30.0 milliamperes ac single winding

## Time Delay:

0.05 seconds fixed release time

# NSN 5945-01-410-8745

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp: 115.0 volts ac 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes ac lamp load and 2.0 amperes dc lamp load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 8 wire hook all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300 Mil-std (military Standard): Mil-prf-6106 spec.