## NSN 5945-01-412-7760

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-412-7760

**Overall Length:** 0.375 inches **Overall Diameter:** Between 0.275 inches and 0.335 inches **Environmental Protection:** Fungus proof Winding Quantity: **Purpose For Which Designed:** General **Coil Quantity:** Winding Dc Resistance Rating: 2.3 kilohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 5 terminal single mounting facility **Nonpile-up Main Contact Arrangement:** 1 pole, double throw, one position momentary **Criticality Code Justification:** Feat Time Delay: 0.004 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes ac resistive load and 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc **Special Features:** Failure rate: 1.0 percent per 10, 000 cycles **Test Data Document:** 81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 5 pin all functions **Specification Data:** 81349-mil-r-39016/10 government specification

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5945-01-412-7760

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300