## NSN 5945-01-413-8612

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-413-8612 **Overall Length:** 0.400 inches **Overall Height:** 0.375 inches Overall Width: 0.375 inches Winding Quantity: **Coil Quantity:** Winding Dc Resistance Rating: 6.5 kilohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 8 plug-in terminal single mounting facility **Pile-up Main Contact Form Arrangement:** 2c **Features Provided:** Coil voltage suppression Operating Voltage Rating And Type At Specificationified Temp: 36.0 volts dc 25 degrees celsius single winding **Minimum Differential Electrical Operating Rating:** 20.0 volts Main Contact Load Current Rating At Maximum Rated Voltage: 250.0 milliamperes ac resistive load and 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc **Test Data Document:** 81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 8 pin all functions **Specification Data:** 81349--39016/42-053m government specification Shelf Life: N/a **Unit Of Measure:** 

Fiig: A03300

No

**Demilitarization:** 

## NSN 5945-01-413-8612

Electromagnetic Relay - Page 2 of 2



Mil-std (military Standard):

Mil-prf-39016 spec.