

View Online at <https://aerobasegroup.com/nsn/5945-01-417-2070>

**Overall Length:**

2.440 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.000 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.000 inches single mounting facility

**Overall Height:**

3.130 inches

**Overall Width:**

2.500 inches

**Environmental Protection:**

Hermetic

**Unthreaded Mounting Hole Diameter:**

0.170 inches single mounting facility

**Winding Quantity:**

2

**Coil Quantity:**

2

**Winding Dc Resistance Rating:**

200.0 ohms all windings

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

**Features Provided:**

Latching contacts and polarized

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

3 pole, double throw, one position momentary

**Time Delay:**

0.035 seconds fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius all windings

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Test Data Document:**

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

13 threaded stud all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300

**Mil-std (military Standard):**

Mil-r-6106 spec.