# NSN 5945-01-418-5651

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-418-5651

## **Overall Length:**

1.718 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.446 inches single mounting facility

#### **Overall Height:**

1.010 inches

#### **Overall Width:**

0.525 inches

#### Mounting Slot Width:

0.150 inches single mounting facility

#### Winding Quantity:

1

#### Coil Quantity:

1

#### Winding Dc Resistance Rating:

280.0 ohms single winding

#### **Duty Type:**

Continuous

#### Mounting Facility Type And Quantity:

2 slotted hole single mounting facility

#### Mounting Facility Pattern:

In-line single mounting facility

#### Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

#### Time Delay:

0.01 seconds fixed release time

#### **Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

#### Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

# Main Contact Maximum Voltage Rating In Volts:

200.0 ac and 280.0 dc

## **Test Data Document:**

81349-mil-r-83536 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### Terminal Type And Quantity:

8 wire hook all functions

#### **Specification Data:**

81349-mil-r-83536/10 government specification

# Shelf Life:

N/a

Unit Of Measure:

# NSN 5945-01-418-5651

Electromagnetic Relay - Page 2 of 2

Demilitarization:

No

Fiig:

A03300

