## NSN 5945-01-420-5891

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-420-5891

**Thread Class:** 

2a single mounting facility

**Thread Length:** 

0.375 inches single mounting facility

**Overall Length:** 

1.531 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.187 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:** 

0.687 inches single mounting facility

**Overall Height:** 

1.812 inches

**Overall Width:** 

1.031 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.687 inches single mounting facility

**Fragility Factor:** 

Moderately rugged

Frequency In Hertz:

400.0

Winding Quantity:

**Coil Quantity:** 

1

Winding Dc Resistance Rating:

200.0 ohms single winding

**Duty Type:** 

Continuous

**Mounting Facility Type And Quantity:** 

4 threaded stud single mounting facility

Storage Type:

General purpose warehouse

**Thread Size:** 

0.375 inches single mounting facility

**Mounting Facility Pattern:** 

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:** 

2 pole, double throw, one position momentary

Time Delay:

0.020 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

## NSN 5945-01-420-5891

Electromagnetic Relay - Page 2 of 2



## Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

115.0 ac

**Special Features:** 

Magnetic latch operation

**Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

10 tab, solder lug all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A03300