

View Online at <https://aerobasegroup.com/nsn/5945-01-420-5891>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

1.531 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.187 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.687 inches single mounting facility

**Overall Height:**

1.812 inches

**Overall Width:**

1.031 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.687 inches single mounting facility

**Fragility Factor:**

Moderately rugged

**Frequency In Hertz:**

400.0

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

200.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 threaded stud single mounting facility

**Storage Type:**

General purpose warehouse

**Thread Size:**

0.375 inches single mounting facility

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

**Time Delay:**

0.020 seconds fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

10.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac

**Special Features:**

Magnetic latch operation

**Thread Series Designator:**

Unc single mounting facility

**Terminal Type And Quantity:**

10 tab, solder lug all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300