# NSN 5945-01-426-5316

Electromagnetic Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-01-426-5316

# **Overall Length:**

1.280 inches

# Center To Center Distance Between Mounting Facilities Parallel To Length:

1.070 inches single mounting facility

# **Overall Height:**

0.640 inches

# **Overall Width:**

0.810 inches

### Mounting Slot Width:

0.133 inches single mounting facility

## Winding Quantity:

1

# Coil Quantity:

1

## Duty Type:

Continuous

## Mounting Facility Type And Quantity:

3 slotted hole single mounting facility

# **Mounting Facility Pattern:**

Triangle single mounting facility

# Nonpile-up Main Contact Arrangement:

3 pole, double throw, one position momentary

# Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

0.500 inches single mounting facility

# Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 10.0 amperes dc resistive load

# Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

# **Test Data Document:**

81349-mil-r-83536 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

11 wire hook all functions

### **Specification Data:**

81349-mil-r-83536/22 government specification

### Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A03300