

View Online at <https://aerobasegroup.com/nsn/5945-01-431-1157>

End Application:

Switchboard, mn prop, p/n 1648a34g06, used onboard 400 ft wagb coast guard vessels

Frequency In Hertz:

60.0

Coil Quantity:

1

Duty Type:

Intermittent

Mounting Facility Type And Quantity:

2 threaded hole single mounting facility

Operating Current Rating And Type:

2.0 amperes ac all windings

Time Delay:

60.00 seconds fixed operate and release time

Auxiliary Contact Maximum Voltage Rating In Volts:

48.0 ac

Minimum Differential Electrical Operating Rating:

10.0 volts

Main Contact Load Current Rating At Maximum Rated Voltage:

0.3 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

1.3 ac

Special Features:

Mounts on basic 4 or 6 pole relay using 2 screws; has 1 n.O. Solid state contact; on delay or off delay applications; will switch 120 volt ac and dc coils; artd is field convertible to 24 or 48 volts dc; time delay, seconds 30-60 art-onb on delay, art-ofb off delay, ac

Terminal Type And Quantity:

2 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300