

View Online at <https://aerobasegroup.com/nsn/5945-01-451-8441>

Overall Length:

5.750 inches

Overall Height:

4.440 inches

Overall Width:

4.750 inches

End Application:

F15s

Current Rating:

5.000 amperes

Voltage In Volts And Current Type:

28.0 dc

Special Features:

Ename on dwg contactor, 3 pdt, 115/200vac, 400 hz, 260 amp; continuous duty cycle; operate coil voltage 28 vdc (max 30 vdc); pickup voltag (max) 18 vdc; dropout 2-7 vdc; closing time (max) 36 ms; release time(max)36 ms; transfer time (max) .015 sec at 18-30vdc; contact bounce (max) 2ms; simultaneous operation (max) 5ms; transient suppression plus or minus 42 vdc; coil current p.U. 4.0 amps hold .7 amperes 25c; main contacts; resistive and inductive 260 amps; overload 2000 amps; rupture 2500 amps; hermetically sealed; environmental operating temp minus 55 degree c to plus 71 degree c; altitude 80, 000 feet max; life electrical 50, 000 cycles , life mechanical 100, 000 cycles ; connector to mate with ms27467t15b; 8s

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli