NSN 5945-01-451-8441

Power Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-01-451-8441

Overall Length:
5.750 inches
Overall Height:
4.440 inches
Overall Width:
4.750 inches
End Application:
F15s
Current Rating:
5.000 amperes
Voltage In Volts And Current Type:
28.0 dc
Special Features:
Ename on dwg contactor, 3 pdt, 115/200vac, 400 hz, 260 amp; continuous duty cycle; operate coil voltage 28 vdc (max 30 vdc); pickup
voltag (max) 18 vdc; dropout 2-7 vdc; closing time (max) 36 ms; release time(max)36 ms; transfer time (max) .015 sec at 18-30vdc; contact
bounce (max) 2ms; simultaneous operation (max) 5ms; transient suppression plus or minus 42 vdc; coil current p.U. 4.0 amps hold .7
amperes 25c; main contacts; resistive and inductive 260 amps; overload 2000 amps; rupture 2500 amps; hermetically sealed; environmental
operating temp minus 55 degree c to plus 71 degree c; altitude 80, 000 feet max; life electrical 50, 000 cycles, life mechanical 100, 000
cycles; connector to mate with ms27467t15b; 8s
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli