

View Online at <https://aerobasegroup.com/nsn/5945-01-461-9953>

Overall Length:

1.718 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.396 inches single mounting facility and 1.446 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches single mounting facility

Overall Height:

1.010 inches

Overall Width:

1.025 inches

Mounting Slot Width:

0.150 inches single mounting facility

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Pile-up Main Contact Form Arrangement:

3c

Features Provided:

Coil voltage suppression

Mounting Facility Pattern:

Triangle single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

0.312 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

13.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

12.0 amperes dc inductive load and 15.0 amperes ac inductive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

3pdt, 25 amp (resistive), hermetically sealed, 28 vdc coil, 3% failure rate, raised vertical flange mount, relay

Terminal Type And Quantity:

9 wire hook contacts

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300

Mil-std (military Standard):

Mil-prf-6106 spec.