

View Online at <https://aerobasegroup.com/nsn/5945-01-461-9953>

**Overall Length:**

1.718 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.396 inches single mounting facility and 1.446 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.625 inches single mounting facility

**Overall Height:**

1.010 inches

**Overall Width:**

1.025 inches

**Mounting Slot Width:**

0.150 inches single mounting facility

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Pile-up Main Contact Form Arrangement:**

3c

**Features Provided:**

Coil voltage suppression

**Mounting Facility Pattern:**

Triangle single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:**

0.312 inches single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:**

13.5 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

12.0 amperes dc inductive load and 15.0 amperes ac inductive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Special Features:**

3pdt, 25 amp (resistive), hermetically sealed, 28 vdc coil, 3% failure rate, raised vertical flange mount, relay

**Terminal Type And Quantity:**

9 wire hook contacts

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300

**Mil-std (military Standard):**

Mil-prf-6106 spec.