

View Online at <https://aerobasegroup.com/nsn/5945-01-463-3569>

Overall Length:

1.718 inches

Overall Height:

1.010 inches

Overall Width:

1.025 inches

Environmental Protection:

Hermetic

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 bracket single mounting facility

Pile-up Main Contact Form Arrangement:

3c

Mounting Facility Pattern:

Triangle single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.396 inches single mounting facility and 1.446 inches single mounting facility

Main Contact Load Current Rating At Maximum Rated Voltage:

12.0 amperes dc inductive load and 15.0 amperes ac inductive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

3pdt, 25 amp (resistive), hermetically sealed, 28 vdc coil, 3% per 10,000 failure rate, raised vertical flange mount, relay

Test Data Document:

81349--83536 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 pin energizing element

Specification Data:

81349-mil-prf-83536/32-003I government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-prf-83536 spec.