

View Online at <https://aerobasegroup.com/nsn/5945-01-463-8973>

Overall Length:

0.370 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.100 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.100 inches single mounting facility

Overall Height:

0.398 inches

Overall Width:

0.370 inches

Environmental Protection:

Hermetic

End Application:

C-17a aircraft e/i fscm 81349

Winding Quantity:

2

Coil Quantity:

1

Winding Dc Resistance Rating:

500.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

Printed circuit terminal single mounting facility

Pile-up Main Contact Form Arrangement:

1c

Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes dc resistive load

Special Features:

Low level to 1 amp, pwb, spdt relay. Rated 12.0 vdc coil with 3% failure rate.

Test Data Document:

81349-mil-prf-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 wire lead contacts

Specification Data:

81349-m-39016/07-034l government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300

Mil-std (military Standard):

Mil-prf-39016 spec.