

View Online at <https://aerobasegroup.com/nsn/5945-01-463-8973>

**Overall Length:**

0.370 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.100 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.100 inches single mounting facility

**Overall Height:**

0.398 inches

**Overall Width:**

0.370 inches

**Environmental Protection:**

Hermetic

**End Application:**

C-17a aircraft e/i fscm 81349

**Winding Quantity:**

2

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

500.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

Printed circuit terminal single mounting facility

**Pile-up Main Contact Form Arrangement:**

1c

**Operating Voltage Rating And Type At Specificationified Temp:**

12.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

1.0 amperes dc resistive load

**Special Features:**

Low level to 1 amp, pwb, spdt relay. Rated 12.0 vdc coil with 3% failure rate.

**Test Data Document:**

81349-mil-prf-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 wire lead contacts

**Specification Data:**

81349-m-39016/07-034l government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300

**Mil-std (military Standard):**

Mil-prf-39016 spec.