

View Online at <https://aerobasegroup.com/nsn/5945-01-463-9427>

Overall Length:

1.718 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.396 inches single mounting facility and 1.446 inches single mounting facility

Overall Height:

1.310 inches

Overall Width:

0.525 inches

Mounting Slot Width:

0.150 inches single mounting facility

Environmental Protection:

Hermetic

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

320.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 slotted hole single mounting facility

Features Provided:

Polarized

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

Special Features:

Temp range minus 70.0 degrees to plus 125.0 degrees c; pickup voltage 18.0 vdc max; hold voltage 7.0 vdc; drop-out voltage 1.5 vdc min; coil current 0.11 amp max; terminal strength 5.0 lbs ; pins are underplated (except polarizing pin is tinned) prior to gold plating (per mil-g-45204, type ii, class i) with nickel 50.000 to 150.000 microinches thick; pins are 0.062 inch diameter and 0.270 inch length with exception of polarizing pin which is 0.300 inch length; 0.050 inch thickness silicone rubber gasket per ams 3332, with shore hardness of 20, is located against bottom of case and at base of pins

Precious Material And Location:

Terminals gold

Terminal Type And Quantity:

8 pin all functions

Shelf Life:

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300