

View Online at <https://aerobasegroup.com/nsn/5945-01-464-2505>

Overall Length:

1.010 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.396 inches single mounting facility and 1.446 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches single mounting facility

Overall Height:

1.025 inches

Overall Width:

1.718 inches

Mounting Slot Width:

0.150 inches single mounting facility

Case Material:

Metal

Environmental Protection:

Hermetic

End Application:

Siu unit 4010 e/i fscm 52088

Frequency In Hertz:

50.0 or 400.0

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 slotted hole single mounting facility

Pile-up Main Contact Form Arrangement:

4c

Mounting Facility Pattern:

Rectangular single mounting facility

Time Delay:

0.05 seconds fixed release time

Main Contact Load Current Rating At Maximum Rated Voltage:

2.9 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Test Data Document:

81349--83536 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

14 wire hook all functions

Specification Data:

81349--83536/17-007 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-prf-83536 spec.