

View Online at <https://aerobasegroup.com/nsn/5945-01-464-2505>

**Overall Length:**

1.010 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.396 inches single mounting facility and 1.446 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.625 inches single mounting facility

**Overall Height:**

1.025 inches

**Overall Width:**

1.718 inches

**Mounting Slot Width:**

0.150 inches single mounting facility

**Case Material:**

Metal

**Environmental Protection:**

Hermetic

**End Application:**

Siu unit 4010 e/i fscm 52088

**Frequency In Hertz:**

50.0 or 400.0

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 slotted hole single mounting facility

**Pile-up Main Contact Form Arrangement:**

4c

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Time Delay:**

0.05 seconds fixed release time

**Main Contact Load Current Rating At Maximum Rated Voltage:**

2.9 amperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:**

28.0 dc

**Test Data Document:**

81349--83536 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

14 wire hook all functions

**Specification Data:**

81349--83536/17-007 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300

**Mil-std (military Standard):**

Mil-prf-83536 spec.