

View Online at <https://aerobasegroup.com/nsn/5945-01-464-3854>

Overall Length:

1.718 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.396 inches single mounting facility and 1.446 inches single mounting facility

Overall Height:

1.010 inches

Overall Width:

0.525 inches

Mounting Slot Width:

0.150 inches single mounting facility

Case Material:

Metal

Environmental Protection:

Hermetic

End Application:

2320-01-123-1610

Frequency In Hertz:

400.0

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

320.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 slotted hole single mounting facility

Features Provided:

Polarized

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

Operating Current Rating And Type:

110.0 milliamperes dc single winding

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

12.0 amperes dc inductive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349--6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

5 pin all functions

Specification Data:

81349--6106/19-005 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300