

View Online at <https://aerobasegroup.com/nsn/5945-01-464-4463>

**Overall Length:**

1.718 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.625 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.396 inches single mounting facility and 1.446 inches single mounting facility

**Overall Height:**

1.025 inches

**Overall Width:**

1.010 inches

**Mounting Slot Width:**

0.150 inches single mounting facility

**Environmental Protection:**

Hermetic

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

260.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 slotted hole single mounting facility

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

3 pole, double throw, one position momentary

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

12.0 amperes dc inductive load and 15.0 amperes ac inductive load

**Main Contact Maximum Voltage Rating In Volts:**

200.0 ac

**Special Features:**

28vdc, 3pdt, 25amp, horizontal flange mount, 3% failure rate, relay

**Test Data Document:**

81349-mil-prf-83536 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

11 solder stud all functions

**Specification Data:**

81349-mil-prf-83536/32 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300

**Mil-std (military Standard):**

Mil-prf-83536 spec.