

View Online at <https://aerobasegroup.com/nsn/5945-01-465-6337>

**Overall Length:**

4.520 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.750 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.880 inches single mounting facility

**Overall Height:**

3.090 inches

**Overall Width:**

3.250 inches

**Environmental Protection:**

Watertight

**Unthreaded Mounting Hole Diameter:**

0.164 inches single mounting facility

**End Application:**

E/i supply class aoe

**Winding Quantity:**

1

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

6 unthreaded hole single mounting facility

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

**Time Delay:**

0.10 seconds adjustable operate time and 1.00 seconds adjustable operate time

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

15.0 amperes dc resistive load and 10.0 amperes ac resistive load

**Main Contact Maximum Voltage Rating In Volts:**

110.0 dc and 480.0 ac

**Special Features:**

Dpdt, 28 vdc coil, on delay electropneumatic timing relay

**Terminal Type And Quantity:**

8 screw all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300