

View Online at <https://aerobasegroup.com/nsn/5945-01-469-3035>

Overall Length:

6.230 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.880 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.750 inches single mounting facility

Overall Height:

3.090 inches

Overall Width:

3.250 inches

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.199 inches single mounting facility

End Application:

Spurdance class dd

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

6 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

1.00 seconds adjustable operate and release time and 10.00 seconds adjustable operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

120.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 500.0 milliamperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac

Terminal Type And Quantity:

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300